



Polar diagram



Cone diagram



Luminous emittance 1 / UGR diagram

Glare evaluation according to UGR												
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	70	70
ρ Walls	50	30	50	30	30	50	30	50	30	30	50	30
ρ Floor	20	20	20	20	20	20	20	20	20	20	20	20
Room size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis						
2H	2H	14.5	15.3	15.2	16.0	16.9	17.4	18.3	18.2	19.0	19.9	
	3H	15.1	15.8	15.8	16.6	17.5	18.4	19.1	19.1	19.9	20.8	
	4H	15.3	16.0	16.1	16.7	17.7	18.7	19.4	19.5	20.2	21.1	
	6H	15.4	16.1	16.2	16.9	17.8	18.9	19.6	19.7	20.3	21.3	
	8H	15.5	16.1	16.3	16.9	17.9	18.9	19.6	19.8	20.4	21.3	
4H	12H	15.5	16.1	16.3	16.9	17.9	19.0	19.5	19.8	20.3	21.3	
	2H	15.0	15.7	15.8	16.4	17.4	17.4	18.2	18.2	18.9	19.8	
	3H	15.7	16.3	16.5	17.1	18.1	18.5	19.1	19.4	19.9	20.9	
	4H	16.0	16.5	16.8	17.3	18.3	19.0	19.5	19.8	20.3	21.3	
	6H	16.2	16.7	17.1	17.5	18.6	19.3	19.7	20.1	20.6	21.6	
8H	8H	16.3	16.7	17.2	17.6	18.6	19.3	19.7	20.2	20.6	21.7	
	12H	16.4	16.7	17.3	17.6	18.7	19.4	19.7	20.3	20.6	21.7	
	4H	16.2	16.6	17.0	17.4	18.5	18.9	19.3	19.8	20.2	21.2	
	6H	16.5	16.8	17.4	17.7	18.8	19.3	19.6	20.2	20.5	21.6	
	8H	16.6	16.9	17.5	17.8	18.9	19.4	19.7	20.3	20.6	21.7	
12H	12H	16.8	17.0	17.7	17.9	19.1	19.5	19.7	20.4	20.6	21.8	
	4H	16.1	16.5	17.0	17.4	18.5	18.9	19.2	19.8	20.1	21.2	
	6H	16.5	16.8	17.4	17.7	18.8	19.3	19.5	20.2	20.4	21.6	
	8H	16.7	16.9	17.6	17.8	19.0	19.4	19.6	20.3	20.5	21.7	
Variation of the observer position for the luminaire distances S												
S = 1.0H		+0.3 / -0.5					+0.1 / -0.2					
S = 1.5H		+0.6 / -1.1					+0.5 / -0.6					
S = 2.0H		+1.1 / -1.7					+1.3 / -1.3					
Standard table		BK04					BK04					
Correction summand		-3.6					-0.6					
Corrected glare indices referring to 1092lm Total luminous flux												

The UGR values are calculated in acc. with CIE Publ. 117. Spacing-to-Height-Ratio = 0.25